(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 14 July 2005 (14.07.2005)

PCT

(10) International Publication Number WO 2005/064701 A2

(51) International Patent Classification7:

H01L 41/09

(21) International Application Number:

PCT/IB2004/052868

(22) International Filing Date:

20 December 2004 (20.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

03104892.9

22 December 2003 (22.12.2003) El


(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): KONINKLIJKE

PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

- (71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Steindamm 94, 20099 Hamburg (DE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KLEE, Mareike, K. [DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). RIJKS, Theodoor, G., S., M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LOK, Pieter [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). MAUCZOK, Ruediger, G. [DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agents: ELEVELD, Koop, J. et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

[Continued on next page]

(54) Title: ELECTRONIC DEVICE



(57) Abstract: The microelectromechanical system (MEMS) element (101) comprises a first electrode (310 that is present on a surface of a substrate (30) and a movable element (40). This overlies at least partially the first electrode (31) and comprises a piezo-electric actuator, which movable element (40) is movable towards and from the substrate (30) by application of an actuation voltage between a first and a second position, in which first position it is separated from the substrate (30) by a gap. Herein the piezoelectric actuator comprises a piezoelectric layer (25) that is on opposite surfaces provided with a second and a third electrode (21,22) respectively, said second electrode (21) facing the substrate (30) and said third electrode (22) forming an input electrode of the MEMS element (101), so that a current path between through the MEMS element (101) comprises the piezoelectric layer (25) and the tunable gap.



KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU. TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.